



SEAL TOUCH GLOW 2™ All-In-One Waterproof Keyboard

Model S87P2

According to a University of North Carolina study, “25% of hospital keyboards harbor the Super Bug MRSA, but daily disinfecting of the keyboards could reduce the risk of cross contamination.” Now, the Association for Professionals in Infection Control and Epidemiology (APIC) includes “cleaning and disinfection of keyboards” for C. Diff prevention.

The SEAL TOUCH GLOW 2™ washable ergo keyboard has been developed to help prevent the spread of infections, including MRSA and C. Diff. The SILVER WAVE™ keyboard is 100% waterproof and can even be disinfected with bleach. As an added safeguard, it includes antimicrobial product protection. The combination of waterproof technology and antimicrobial product protection achieves the highest level of protection available in a true type keyboard today.



- 100% Waterproof Guaranteed
- Limited Lifetime Warranty
- Silver Seal™ Antimicrobial Product Protection
- Quick Connect™ cable
- Seal Cap™ protects USB connector
- Built-in Seal Touch™ touch pad
- Lighter weight, improved tactile feel, smaller footprint
- Improved touchpad integration and keyboard layout
- Custom mounting solutions available for special orders
- Patent Pending



[See back for specifications](#)



S87P2 Seal Touch™ Silicone All-in-One Keyboard with Touch Pad
 87 key layout
 UV-Reinforced printed keys resist fading
 Built-in touch pad for pointing and mouse functionality



Silver Seal™ Protection. This product is Silver Seal™ protected. It contains an antimicrobial, fungistatic agent which protects the product and keeps it cleaner, greener and fresher by inhibiting the growth of microbial bacteria, mold, mildew and fungi on the product's surface.



Technical Specifications

Compatibility:	Windows, Mac (USB models)
Key layout:	87 keys
Dimensions	
L x W x H:	12.25 in. x 8.1 in. x 0.5 in.
Weight:	1.6 lbs.
Cable Length:	6in (15cm) Quick Connect™ with USB extension cable
Connection Types:	Gold-plated USB
Key Switch:	Carbon point activation with tactile feedback
Key Switch Operating Force:	160 ±15gf
Key Switch Life Cycle:	Greater than 10 million keystrokes
Keycaps Type:	UV Reinforced Printing
Total Key Travel:	.07 ± .0196 in (1.6 ±0.5mm)
Operating Voltage:	+5VDC ± 5%
Power Consumption:	≤100mA
EMI - RFI:	Conforms to FCC rules for a Class B computing device
Approvals/Certifications/Ratings:	IP 68, NEMA 4X, RoHS, WEEE, CE, FCC
Waterproof and Dustproof Ratings:	100% Waterproof and Dustproof (IP 68, NEMA 4X)

SEAL SHIELD™ Protects Against		
Water	Solvents	Salt Water
Disinfectants	Humidity	Abrasives
Dust	Corrosives	Dirt
Sand	Shock	Alkaline
Alcohol	Bleach	Acid
Blood	Heat	Cold



Windows®/Mac® Compatible

Mac Compatibility requires OS X 10.5 or later. See product manual for details.

Mac® is a trademarks of Apple Inc., registered in the U.S. and other countries. Windows® is a registered trademark of Microsoft, Inc. Copyright© 2013, Seal Shield, LLC. All rights reserved. All brand and trade names are registered trademarks of their respective owners.

Seal Shield, LLC
 Jacksonville, FL 32205
 Made in China

SSKSV104-06272013